

# KODAK PIXPRO SP360 4K

## 360° VR CAMERA



## SP360 4K

Prepare to enter the next frontier of 360° interactive video and transcend the ordinary. Introducing the KODAK PIXPRO SP360 4K VR Camera, designed to take your creative vision to the next level. 4K resolution\* adds ample detail, clarity and precision for important nuances you want to capture and share. Experience the flexibility, power and performance of the SP360 4K and take your 360° VR video content to new heights. KODAK PIXPRO Digital Cameras – Tell your story.

### FEATURES:

- Facebook™ and YouTube™ 360° Videos\*\*
- 4K Equivalent VR Video\*
- 235° FOV / Ultra Wide Lens
- Control Wirelessly with iOS™ / ANDROID™ Smart Device APP
- RF Remote Control (sold separately)
- Supports MicroSD Card Up To 128GB (Class 10 or Higher)

### PIXPRO Supported Software

Desktop Editing Software, Desktop Stitch Software



\*\*SP360 4K supports Facebook™ 360° Video



\*\*SP360 4K supports YouTube™ 360° Video

\*4K refers to 8 million plus pixel resolution at [1:1] aspect ratio



# KODAK PIXPRO SP360 4K

## 360° VR CAMERA

| SPECIFICATIONS                               | SP360 4K   |
|--|--|
| Effective Image Sensor Pixels                | 12.40 Megapixels   |
| Total Image Sensor Pixels                    | 12.76 Megapixels [1/2.33" BSI CMOS]  |
| Lens   |  |
| Focal Length<br>[ 35mm film equivalent ]     | 0.850 mm<br>[8.20 mm]  |
| F number                                     | F2.8   |
| Lens Construction                            | 7 groups 9 elements  |
| Optical Zoom                                 | Fix Focus  |
| Field of View                                | Max. 235 Degree (Without Lens Cover)   |
| Focusing Range                               | 50 cm — ∞  |
| Anti-Handshake                               | Electronic Image Stabilization (EIS)   |
| Number of Recording Pixels                   |  |
| Still Image                                  | (1:1) 8MP: 2880x2880, (4:3) 4MP: 2304x1728, (16:9) 2MP: 1920x1080  |
| Video  | Round Video: 2880x2880: 30fps (1:1), 2048x2048: 30fps (1:1), 1440x1440: 60fps/30fps (1:1), 1072x1072: 60fps/30fps (1:1)<br>Flat Video: (3840x2160): 30fps (16:9), 1920x1080: 60fps/30fps (16:9), 1280x720: 60fps/30fps (16:9), 848x480: 60fps (16:9)<br>High Speed Video: 720x720: 120fps (1:1), 1280x720: 120fps (16:9), 848x480: 240fps (16:9) |
| File Format                                  |  |
| Still Image                                  | Exif 2.3 (JPEG)  |
| Movie  | MP4 [Image: H.264; Audio: AAC [Stereo]]  |
| Shooting Modes                               | Still, Burst Shot, Movie, Time Lapse, Loop Recording, Hi-Speed Movie   |
| Splashproof                                  | Equivalent to JIS/IEC IPX5 (Body)  |
| Shockproof                                   | Up to 2m (With Protective Lens Cover)  |
| Dustproof                                    | Equivalent to JIS/IEC (IP6X)   |
| Freezeproof                                  | 14° F / - 10° C  |
| Status LCD                                   | 1.0 inch TN LCD  |
| Level Gauge                                  | 3-Axis   |
| ISO Sensitivity                              | Auto, (100 - 800)  |
| Exposure Metering Method                     | Artificial Intelligence AE (AiAE)  |
| Exposure Control Method                      | Program AE   |
| Burst Mode                                   | Approx. 10fps (Full Resolution)  |
| White Balance Control                        | Auto (AWB), Daylight, Cloudy, Fluorescent, Incandescent, Underwater  |
| Recording Media                              | Micro SD/Micro SDHC Card/Micro SDXC Card (Up to 128GB Support) [MMC Card Not Supported] Use Class 10 Card or Higher  |
| Language Support                             | English  |
| Jacks  | USB 2.0 (Micro 5 pin USB), HDMI (Type D)   |
| Wi-Fi  | Yes (802.11 b/g/n)   |
| NFC  | Yes  |
| Remote Control                               | Yes (via Smart Device), RF Remote Control, Control up to 5 Cameras, (Sold Separately)  |
| Power  | Rechargeable Li-ion Battery (LB-080), 3.6V 1250mAh, In-Camera Charging   |
| Shooting Capability<br>(Battery Performance) | Approx. 160 Shots (Based on CIPA Standards)(Wi-Fi On)<br>Approx. 55 min. for Video (@ 4K/30fps) (Wi-Fi-On)   |
| Operation Environment                        | Temperature: 14° - 104°F / -10° - 40°C, Humidity: 0 - 90%  |
| Dimensions (WxHxD)                           | Approx. 1.88 x 1.96 x 2.06 in. / 48.0 x 50.0 x 52.5 mm (Based on CIPA Standards) (Without Lens Cover)  |
| Weight                                       | Approx. 3.59 oz. / 102g (Body Only), Approx. 128g (With Battery and Micro SD Card)   |
| Supplied Accessories                         | Rechargeable Li-ion Battery, USB Cable, AC Adapter, Quick Start Guide, Lens Cover, Protective Cover, Lens Ring, Small Lens Cover Case, Battery Charger, Carrying Case, Cleaning Cloth, SP360 4K Overview Card and SP360 4K Online Company Store Card, Warranty Card, Service Card, SP360 4K Best Practices Card                                  |
| Compatible Devices                           | iOS™ Devices (version 8.0 and up) / Android™ Devices (version 4.2 and up) supported.<br>(iPad mini 1/ iPad 2/ iPhone 4s and below not supported.)  |

\*4K refers to 8 million plus pixel resolution at [1:1] aspect ratio

## JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248  
(888) 978-0806

© 2023 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0037.0718.en.12



To learn more about KODAK PIXPRO Digital Cameras:  
visit: [kodakpixpro.com](http://kodakpixpro.com)

