

KODAK PIXPRO FZ43

DIGITAL CAMERA



FZ43 FRIENDLY ZOOM

Introducing the FZ43, Friendly Zoom model from the KODAK PIXPRO collection of digital cameras. Compact, intuitive and oh so easy to use, the FZ43 is the perfect camera to take anywhere you go. One-touch video, red-eye removal, face detection and convenient AA batteries are just the start. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 4X Optical Zoom
- 27 mm Wide Angle
- 16 MP
- 2.7" LCD
- 720p HD Video
- AA Batteries

4X
Optical
Zoom

27mm
WIDE

16MP

2.7" LCD

720p
HD Video

**Panorama
Capture**



Available Colors:

- BLACK
- RED

Images are simulated.



KODAK PIXPRO FZ43

DIGITAL CAMERA

SPECIFICATIONS		FZ43
Effective Image Sensor Pixels	16.15 Megapixels	
Total Image Sensor Pixels	16.44 Megapixels [1/2.3"(CCD)]	
Lens	4.9 mm (Wide) — 19.6 mm (Tele)	
Focal Length [35mm film equivalent]	[27 mm (Wide) — 108 mm (Tele)]	
F number	F3.0 (Wide) — F6.6 (Tele)	
Lens Construction	7 groups 7 elements	
Optical Zoom	4x	
Focusing Range	Normal: (Wide) 60 cm — ∞, (Tele) 100 cm — ∞ Macro: 5 cm — ∞ (Wide Only)	
Anti-Handshake	Digital Image Stabilization	
Digital Zoom	6x Digital Zoom (Combined Zoom: 24x)	
Number of Recording Pixels		
Still Image	(4:3) 16MP: 4608x3456, 10MP:3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080	
Movie	1280x720 (30/15fps), 640x480 (30fps), 320x240 (30fps)	
Image Compression	Best, Fine, Normal	
File Format		
Still Image	Exif 2.3 (JPEG)	
Movie	MOV [Image: Motion JPEG; Audio: G.711 (Monaural)]	
Shooting Modes	M, Auto, Movie, Panorama, SCN	
SCN Modes	ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Snow, Children, ID, Glass, Photo Frame, Panning Shot, Text, Portrait, Fish Eye, Party, Indoor, Leaf, Museum, Night Portrait, Sketch, Imaging Stabilization	
Detection Features	Face, Smile, Blink	
Photo Touch-up	Red-Eye Removal	
Panorama Capture	0° - 180° (Horizontal)	
LCD Display	2.7 inch (230K Pixels)	
ISO Sensitivity	Auto, ISO80/100/200/400/800/1600	
AF Method	Single AF, Multi-AF (TTL 9-point), Face Detection	
Exposure Metering Method	Artificial Intelligence AE (AiAE), Face AE	
Exposure Control Method	Program AE (AE-Lock Available)	
Exposure Compensation	+/- 2EV in 1/3 Step Increments	
Shutter Speed	1/2000 - 4 Seconds	
Continuous Shooting	Yes	
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Zoom (Approx. x2 - x8)	
White Balance Control	Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent, Manual	
Flash		
Flash Method	Internal	
Flash Modes	Auto, Red-Eye Reduction, Forced Flash, No Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro	
Shooting Range	(Wide) Approx. 0.3 m - 5.2 m (ISO800); (Tele) Approx. 0.5 m - 2.4 m (ISO800)	
Recording Media	Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported]	
Other Features	PictBridge, ExifPrint Support, Multi-Language Support (27 Languages)	
Jacks	AV-OUT/USB 2.0 (Micro 5-pin USB)	
Power	AA Alkaline Battery (x2), AA NiMH Battery (x2) (Not Included)	
Shooting Capability (Battery Performance)	Approx. 120 Shots of AA Alkaline Battery (Based on CIPA Standards)	
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%	
Dimensions (WxHxD)	Approx. 93.0 x 60.2 x 28.7 mm / 3.66 x 2.37 x 1.12 in. (Based on CIPA Standards)	
Weight	Approx. 4.1 oz. / 117g (Body Only)	
Supplied Accessories	AA Alkaline Battery(x2), USB Cable, Wrist Strap, Quick Start Guide, Warranty Card, Service Card	

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248
(888) 978-0806

© 2021 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0029.0321.en.07

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

